



Configuring a remote SMTP Server to work with infoRouter

Using a remote SMTP server to send email messages from infoRouter

If you wish to send email messages from infoRouter using a remote SMTP Server, you must follow these steps.

- Configure remote SMTP Server to relay email messages based on authentication.
- Identify the remote SMTP Server to infoRouter by registering the SMTP Server in the infoRouter web.config file.
- Before you enter a user id and password into the web.config file, verify that the credentials you use work by setting up this account in an e-mail client program such as MS Outlook. Verify that you can receive and send emails with these credentials. Once verified, enter the exact values into the web.config file. Refer to the next page on where to specify these values.

infoRouter Web.config file

```
<configuration>
  <appSettings>
    <add key="ApplicationPath" value="C:\InfoRouter" />
    <add key="ServiceTimerPeriod" value="1" />
    <add key="ProfileExpirationTime" value="60" />
    <add key="TrustedLDAPAccount" value="" />
    <add key="SysadminCheckAccount" value="" />
    <add key="AUTHENTICATIONAUTHORITIES" value="" />
    <add key="" value="" />
    <add key="CONVERSIONSERVICE_PDF" value="" />
    <add key="IRDOTNET.irsupportservice.srv" value="http://www.actinn.com/support/srv.asmx" />
    <add key="IRDOTNET.UpdateServices.catalog" value="http://www.actinn.com/irservice/catalog.asmx" />
    <add key="TEMPDIR" value="C:\InfoRouter\Temp" />
    <add key="APPLICATIONURL" value="http://some_server/InfoRouter/" />
    <add key="INDEXSRV" value="TRUE" />
    <add key="INDEXCATALOG" value="WHINDEX" />
    <add key="SystemEmailAddress" value="admin@acme.com" />
    <add key="smtpserver" value="NameofSMTPserver" />
    <add key="smtpserverport" value="25" />
    <add key="smtpconnectiontimeout" value="10" />
    <add key="smtpsendusername" value="user name" />
    <add key="smtpsendpassword" value="password" />
    <add key="MaximumDisplayFolderCount" value="500" />
    <add key="CheckSecurityOnSearch" value="TRUE" />
  </appSettings>
```

Edit this section

The web.config file can be found in the site directory under the infoRouter installation folder.

Gmail Example

```
<add key="SystemEmailAddress" value="email@gmail.com" />  
<add key="smtpserver" value="smtp.gmail.com" />  
<add key="smtpserverport" value="587" />  
<add key="smtpconnectiontimeout" value="10" />  
<add key="smtpsendusername" value="email@gmail.com" />  
<add key="smtpsendpassword" value="gmail password" />  
<add key="smtpSSL" value="true"/>
```

You may have to allow GMAIL to allow “Less secure applications” to use the Gmail SMTP.

Make sure that you enter the correct settings for the remote SMTP Server.

Some SMTP Servers are open to relay so they may not require a user ID and password.

Consult your Network Administrator on how to use this SMTP Server.

For additional information on how to install and configure an SMTP server on other Windows platforms visit the support site:

support.inforouter.com

Look for these documents in the Installation & Configuration section

For troubleshooting SMTP issues refer to this guide.

http://www.inforouter.com/Downloads/V80/SMTP_Troubleshooting_V80.pdf